

HP DesignJet T1700 Printer series

The most secure, empowering HP DesignJet printer for CAD/GIS workgroups



SECURE—Protect your work and your information

- Protect printers/data from unauthorized access with HP Secure Boot, whitelisting, encrypted hard disk, more
- Protect documents, preserve confidentiality with authentication solutions like PIN printing, card readers¹
- Secure your printers with HP JetAdvantage Security Manager; manage your fleet remotely with HP Web Jetadmin
- Control and optimize printing costs with accounting solutions—or with your reseller through HP Partner Link

EFFICIENT—No more PC freezing up

- Adobe PDF drivers² free up your computer immediately after sending to print—even for the most complex files
- No interruptions—dual-roll options reduce roll changes; two rolls double capacity, help switch paper types³
- Handle complex files—powerful processing architecture⁴, 128 GB memory⁵, 500 GB HDD at 116 A1/D pgs/hr.
- Easily print project sets and PDF documents with HP Click printing software

ACCURATE—Make better decisions with precise colors

- Get bright color and bold image guality even on plain papers—with HP Bright Office Inks
- Reproduce transparencies, layers, color palettes, and gradients with embedded Adobe PDF Print Engine²
- Tuned profiles reproduce distinct shades of color; color/gray/photo black inks make soft colors, dark tones
- Accurately display data—high-density printheads provide 2400 nozzles per inch. enabling 0.1% line accuracy⁶

For more information, please visit hp.com/go/designjetT1700

Dynamic security enabled printer. Cartridges using a non-HP chip might not work and those that work today might not work in the future. More at: hp.com/go/learnaboutsupplies



Refers exclusively to file processing capabilities for complex files, and does not refer to print speed ⁵ Based on 4 GB DDR3 RAM

¹ Card reader functionality enabled through optional third-party solutions.
² Requires purchase of HP DesignJet T1700 PostScript® models or optional HP DesignJet PostScript/PDF Upgrade Kit. The Adobe PDF Print Engine (APPE) is Adobe's high speed, high fidelity print platform. Version 4 extends APPE's leading edge for print reproduction with new performance efficiencies and breakthrough rendering features. APPE 4 enables printers to increase workflow efficiency and capitalize on the profit potential of innovations in inkjet print technology. To learn more, visit adobe.com/products/pdfprintengine. Dual-roll printing is available on the HP Design Jet T1700dr 44-in Printer and HP Design Jet T1700dr 44-in PostScript® Printers

^{±0.1%} of the specified vector length or ±0.2 mm (whichever greater) at 23° C (73° F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Matte Film and HP Bright Office Inks

Technical specifications

		26 sec/page on A1/D, 116 A1/D prints per hour	
	Print resolution	Up to 2400 x 1200 optimized dpi	
	Margins (top x bottom x left x right)	Roll: 3 x 3 x 3 x 3 mm (0.1 x 0.1 x 0.1 x 0.1 in)	
		Sheet: 3 x 17 x 3 x 3 mm (0.1 x 0.67 x 0.1 x 0.1 in)	
	Technology	HP Thermal Inkjet	
	Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)	
	Ink drop	6 pl	
	Printheads	3 universal printheads, 2 colors each: mK-Y / C-M / G-pK	
	Printhead nozzles	2112 each color	
	Line accuracy	± 0.1% ⁸	
	Minimum line width	0.02 mm (0.0008 in) (PDF addressable @ 1200 dpi)	
Media	Handling	Sheet feed, roll feed, automatic cutter	
	Size	Rolls: 279 to 1118 mm (11 to 44 in) Sheets: 210 x 279 to 1118 x 1676 mm (8.3 x 11 to	
		44 x 66 in)	
		Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E)	
	Thickness	Up to 0.8 mm (31.5 mil)	
Applications	Line drawings, Renderings, Presentations, Maps, Orthophotos		
Memory	128 GB virtual ⁹ 500 G	B Self Encrypted hard disk (AES-256 Encrypted)	
Connectivity	Interfaces	Ethernet, Fast Ethernet, Gigabit Ethernet, 10/100/1000Base-T Ethernet (802.3, 802.3u, 802.3ab); USB Type-A host port	
	Print languages	Basic Printer: HP-GL/2, TIFF, JPEG, URF, CALS G4 PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7 ext 3, HP-GL/2, TIFF, JPEG, URF, CALS G4	
	Printing paths	HP driver for Windows and MAC OS X, direct printing from USB flash drive, email printing, HP Smart app, HP Click printing software, HP Print Service for Android, Apple AirPrint driver	
	Drivers (included)	Basic Printer: Raster drivers for Windows and macOS PostScript Printer: Raster drivers for Windows and macOS; PostScript and PDF Windows drivers and macOS PostScript driver	
Security features	HP Secure Boot, Whitelisting ¹⁰ , Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, self-encrypting HDD, PIN printing		
Dimensions	PIN printing	curity Manager compatible, self-encrypting HDD,	
	PIN printing Printer	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in)	
(w x d x h)	PIN printing Printer Shipping	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in)	
(w x d x h)	PIN printing Printer	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb)	
(w x d x h)	PIN printing Printer Shipping Printer	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb)	
(w x d x h)	PIN printing Printer Shipping	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb) Single-roll printer: 126 kg (278 lb)	
(w x d x h) Weight What's in the	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 f stand, spindle, setup	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb)	
(w x d x h) Weight What's in the box Compatible software and	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 f stand, spindle, setup label kits HP Click, HP Utility fo	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb) Single-roll printer: 126 kg (278 lb) Double-roll printer: 128 kg (282 lb) Printer, printheads, Introductory ink cartridges, printer	
(w x d x h) Weight What's in the box Compatible software and solutions	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 I stand, spindle, setup Label kits HP Click, HP Utility fo Server, HP JetAdvant	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb) Single-roll printer: 128 kg (278 lb) Double-roll printer: 128 kg (282 lb) Printer, printheads, Introductory ink cartridges, printer poster, introductory information, warranty, power cords, r Mac and Windows, HP WebJet Admin, HP Embedded Web	
(w x d x h) Weight What's in the box Compatible software and solutions Environmental	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 f stand, spindle, setup label kits HP Click, HP Utility fo Server, HP JetAdvant Operating temperatu	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb) Single-roll printer: 126 kg (278 lb) Double-roll printer: 128 kg (282 lb) Printer, printheads, Introductory ink cartridges, printer poster, introductory information, warranty, power cords, r Mac and Windows, HP WebJet Admin, HP Embedded Web age Security Manager, HP Partner Link, HP MPS re: 5 to 40°C (41 to 104°F)	
(w x d x h) Weight What's in the box Compatible software and solutions Environmental	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 f stand, spindle, setup label kits HP Click, HP Utility fo Server, HP JetAdvant Operating temperature	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb) Single-roll printer: 126 kg (278 lb) Double-roll printer: 128 kg (282 lb) Printer, printheads, Introductory ink cartridges, printer poster, introductory information, warranty, power cords, r Mac and Windows, HP WebJet Admin, HP Embedded Web age Security Manager, HP Partner Link, HP MPS re: 5 to 40°C (41 to 104°F) :-25 to 55°C (-13 to 131°F)	
w x d x h) Weight What's in the Jox Compatible software and solutions Environmental ranges	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 f stand, spindle, setup Label kits HP Click, HP Utility fo Server, HP JetAdvant Operating temperature Operating humidity: 2	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb) Single-roll printer: 126 kg (278 lb) Double-roll printer: 128 kg (282 lb) Printer, printheads, Introductory ink cartridges, printer poster, introductory information, warranty, power cords, r Mac and Windows, HP WebJet Admin, HP Embedded Web age Security Manager, HP Partner Link, HP MPS re: 5 to 40°C (41 to 104°F) :-25 to 55°C (-13 to 131°F) 20 to 80% RH	
(w x d x h) Weight What's in the box Compatible software and solutions Environmental ranges	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 I stand, spindle, setup Label kits HP Click, HP Utility fo Server, HP JetAdvant Operating temperatu Storage temperature Operating humidity: 2 Sound pressure: 45 d	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb) Single-roll printer: 126 kg (278 lb) Double-roll printer: 128 kg (282 lb) Printer, printheads, Introductory ink cartridges, printer poster, introductory information, warranty, power cords, r Mac and Windows, HP WebJet Admin, HP Embedded Web age Security Manager, HP Partner Link, HP MPS re: 5 to 40°C (41 to 104°F) : -25 to 55°C (-13 to 131°F) 20 to 80% RH B(A) (printing); 32 dB(A) (ready); < 15 dB(A) (sleep)	
(w x d x h) Weight What's in the box Compatible software and solutions Environmental ranges Acoustic	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 I stand, spindle, setup label kits HP Click, HP Utility fo Server, HP JetAdvant Operating temperature Operating temperature Operating humidity: 2 Sound pressure: 45 d Sound power: 6.1 B(A	urity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb) Single-roll printer: 126 kg (278 lb) Double-roll printer: 128 kg (282 lb) Printer, printheads, Introductory ink cartridges, printer poster, introductory information, warranty, power cords, r Mac and Windows, HP WebJet Admin, HP Embedded Web age Security Manager, HP Partner Link, HP MPS re: 5 to 40°C (41 to 104°F) : -25 to 55°C (-13 to 131°F) 20 to 80% RH B(A) (printing); 32 dB(A) (ready); < 15 dB(A) (sleep)) (printing); 5.0 B(A) (ready); < 3.1 B(A) (sleep)	
(w x d x h) Weight What's in the box Compatible software and solutions Environmental ranges Acoustic	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 f stand, spindle, setup label kits HP Click, HP Utility fo Server, HP JetAdvant Operating temperature Operating temperature Operating humidity: 2 Sound pressure: 45 d Sound power: 6.1 B(A < 100 W (printing); < 3 Front End) (sleep); 0.1	Lurity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 72 kg (153 lb) Single-roll printer: 126 kg (278 lb) Double-roll printer: 128 kg (282 lb) Drinter, printheads, Introductory ink cartridges, printer poster, introductory information, warranty, power cords, rMac and Windows, HP WebJet Admin, HP Embedded Web age Security Manager, HP Partner Link, HP MPS re: 5 to 40°C (41 to 104°F) : -25 to 55°C (-13 to 131°F) 20 to 80% RH B(A) (printing); 32 dB(A) (ready); < 15 dB(A) (sleep)) (printing); 5.0 B(A) (ready); < 3.1 B(A) (sleep) 24 W (ready); < 0.3 W (< 6.5 W with embedded Digital W (off)	
(w x d x h) Weight What's in the box Compatible software and solutions Environmental ranges Acoustic Power consumption	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 f stand, spindle, setup label kits HP Click, HP Utility fo Server, HP JetAdvant Operating temperature Operating temperatures Operating humidity: Z Sound pressure: 45 d Sound power: 6.1 B(A < 100 W (printing); < 3 Front End) (sleep); 0.1 Input voltage (auto r.	Lurity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 72 kg (163 lb) Single-roll printer: 126 kg (278 lb) Double-roll printer: 128 kg (282 lb) Drinter, printheads, Introductory ink cartridges, printer poster, introductory information, warranty, power cords, rMac and Windows, HP WebJet Admin, HP Embedded Web age Security Manager, HP Partner Link, HP MPS re: 5 to 40°C (41 to 104°F) : -25 to 55°C (-13 to 131°F) 20 to 80% RH B(A) (printing); 32 dB(A) (ready); < 15 dB(A) (sleep)) (printing); 5.0 B(A) (ready); < 3.1 B(A) (sleep) 24 W (ready); < 0.3 W (< 6.5 W with embedded Digital W (off) anging) 100-240 V (± 10%), 50/60 Hz (± 3 Hz), 2 A max	
(w x d x h) Weight What's in the box Compatible software and solutions Environmental ranges Acoustic Power consumption	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 f stand, spindle, setup label kits HP Click, HP Utility fo Server, HP JetAdvant Operating temperature Operating temperature Operating humidity: 2 Sound pressure: 45 d Sound power: 6.1 B(A < 100 W (printing); < 3 Front End) (sleep); 0.1	Lurity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb) Single-roll printer: 126 kg (278 lb) Double-roll printer: 126 kg (282 lb) Drinter, printheads, Introductory ink cartridges, printer poster, introductory information, warranty, power cords, rMac and Windows, HP WebJet Admin, HP Embedded Web age Security Manager, HP Partner Link, HP MPS re: 5 to 40°C (41 to 104°F) : -25 to 55°C (-13 to 131°F) 20 to 80% RH B(A) (printing); 32 dB(A) (ready); < 15 dB(A) (sleep)) (printing); 5.0 B(A) (ready); < 3.1 B(A) (sleep) 24 W (ready); < 0.3 W (< 6.5 W with embedded Digital W (off)	
Dimensions (w x d x h) Weight What's in the box Compatible software and solutions Environmental ranges Acoustic Power consumption Certification	PIN printing Printer Shipping Printer Shipping HP DesignJet T1700 f stand, spindle, setup label kits HP Click, HP Utility fo Server, HP JetAdvant Operating temperature Operating temperatures Operating humidity: Z Sound pressure: 45 d Sound power: 6.1 B(A < 100 W (printing); < 3 Front End) (sleep); 0.1 Input voltage (auto r.	 curity Manager compatible, self-encrypting HDD, 1802 x 695 x 998 mm (70.9 x 27.4 x 39.3 in) 1955 x 770 x 710 mm (77 x 30.3 x 28 in) Single-roll printer: 72 kg (159 lb) Double-roll printer: 74 kg (163 lb) Single-roll printer: 126 kg (278 lb) Double-roll printer: 128 kg (282 lb) Printer, printheads, Introductory ink cartridges, printer poster, introductory information, warranty, power cords, r Mac and Windows, HP WebJet Admin, HP Embedded Web age Security Manager, HP Partner Link, HP MPS re: 5 to 40°C (41 to 104°F) :-25 to 55°C (-13 to 131°F) 20 to 80% RH B(A) (printing); 32 dB(A) (ready); < 15 dB(A) (sleep)) (printing); 5.0 B(A) (ready); < 3.1 B(A) (sleep) 24 W (ready); < 0.3 W (< 6.5 W with embedded Digital W (off) anging) 100-240 V (± 10%), 50/60 Hz (± 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Singapore (PSB) 	

⁷ Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP inks.

 \pm 0.1% of the specified vector length or \pm 0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on AO/E HP Matte Film in Best or Normal mode with Original HP inks. ⁹ Based on 4 GB DDR3 RAM.

¹⁰ Post intro

¹¹ BMG trademark license code FSC®-C115319, see <u>fsc.org</u>. HP trademark license code FSC®-C017543, see <u>fsc.org</u>. Not all FSC®-certified products are available in all regions. For information about HP large format printing materials, please visit <u>HPLFMedia.com</u>.

¹² Can be recycled through commonly available recycling programs.



Product	W6B55A		HP DesignJet T1700 44-in Printer
	1VD87A		HP DesignJet T1700 44-in PostScript Printer
	W6B56A		HP DesignJet T1700dr 44-in Printer
	1VD88A		HP DesignJet T1700dr 44-in PostScript Printer
Accessories	Q6709A		HP DesignJet 44-in Spindle
	G6H51B		HP HD Pro 42-in Scanner
	G6H50B		HP SD Pro 44-in Scanner
	CN538A		HP DesignJet 3-in Core adapter
	N7P47AA		HP USB 3.0 to Gigabit LAN Adapter
	COC66B		HP DesignJet PostScript/PDF Upgrade Kit
Original HP printhead	P2V27A		HP 731 DesignJet Printhead
Original HP ink cartridges	P2V62A		HP 730 130-ml Cyan DesignJet Ink Cartridge
	P2V63A		HP 730 130-ml Magenta DesignJet Ink Cartridge
	P2V64A		HP 730 130-ml Yellow DesignJet Ink Cartridge
	P2V65A		HP 730 130-ml Matte Black DesignJet Ink Cartridge
	P2V66A		HP 730 130-ml Gray DesignJet Ink Cartridge
	P2V67A		HP 730 130-ml Photo Black DesignJet Ink Cartridge
	P2V68A		HP 730 300-ml Cyan DesignJet Ink Cartridge
	P2V69A		HP 730 300-ml Magenta DesignJet Ink Cartridge
	P2V70A		HP 730 300-ml Yellow DesignJet Ink Cartridge
	P2V71A		HP 730 300-ml Matte Black DesignJet Ink Cartridge
	P2V72A		HP 730 300-ml Gray DesignJet Ink Cartridge
	P2V73A		HP 730 300-ml Photo Black DesignJet Ink Cartridge
Original HP large format printing materials	C6810A		HP Bright White Inkjet Paper (FSC® certified) ¹¹ 🛟 ¹² 914 mm x 91.4 m (36 in x 300 ft)
	C6569C		HP Heavyweight Coated Paper ¹² 1067 mm x 30.5 m (42 in x 100 ft)
	Q6581A		HP Universal Instant-dry Satin Photo Paper (FSC® certified) ¹¹ 🛟 1067 mm x 30.5 m (42 in x 100 ft)
	Q1406B		HP Universal Coated Paper (FSC® certified) ¹¹ ¹² 1067 mm x 45.7 m (42 in x 150 ft)
Service and support	1-roll	2-rolls	
	H4518E	H4518E	HP Installation Service with Network Setup
	U1XV4E	U1XV4E	HP Preventive Maintenance Service
	U9QQ6E	U9QS9E	HP 3 year NBD* Onsite HW Support with DMR**
	U9QQ8E	U9QT1E	HP 5 year NBD* Onsite HW Support with DMR**
	U9QS2PE	U9TQ8PE	HP 1 year Post Warranty NBD* Onsite HW Support with DMR**
	U9QS3PE	U9TQ9PE	HP 2 year Post Warranty NBD* Onsite HW Support with DMR**
	U9TR3E	U9TR4E	HP NBD* Onsite Hardware Subscription Support (per month)

* Next Business Day.

** This services comes with Defective Media Retention (DMR) option that keeps your sensitive data safe. To comply with security regulations you can keep the defective hard drive or data-retentive memory component while getting a replacement disk or memory.

HP DesignJet Support Services offer solutions for business critical environments —installation, extended support and maintenance, as well as a variety of value-added services. For more information, please visit <u>hp.com/go/designjetsupport</u>.

Use **Original HP inks** and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays. For more information, visit hp.com/go/OriginalHPinks.

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.



- ENERGY STAR[®] certified¹ and EPEAT[®] Silver registered²
- Free, convenient HP ink cartridge recycling³
- FSC®-certified papers⁴ and a range of recyclable HP media with a take-back program⁵
 Designed with the environment in mind—made from 30% post-consumer recycled plastic
- ¹ ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental
- Protection Agency. EPEAT® registered where applicable. EPEAT registration varies by country. See www.epeat.net for registration
- status by country.
- status by country. Program availability varies. Please check www.hp.com/recycle for details. BMG trademark license code FSC®-C115319, see <u>fsc.org</u>. HP trademark license code FSC®-C017543, see <u>fsc.org</u>. Not all FSC®-certified products are available in all regions. Many HP printing materials are recyclable through commonly available recycling programs. For information about HP large format printing materials, please visit <u>HPLFMedia.com</u>. 5

Please recycle large-format printing hardware and printing supplies. Find out how at our website

hp.com/ecosolutions



© Copyright 2018 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set for th in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

